

No. P00100194

Order No. 199932194

Applicant Weidmüller Interface GmbH & Co.
Paderborner Strasse 175
D-32760 Detmold
GERMANY

Manufacturer Weidmüller Interface GmbH & Co.
Paderborner Strasse 175
D-32760 Detmold
GERMANY

Factory Weidmüller Interface GmbH & Co.
Paderborner Strasse 175
D-32760 Detmold
GERMANY

Group 06 74500 Terminal blocks for incorporation, for fixation to a support; for industrial use etc.
(EN 60947-7-1)

Model/type WDK 2.5

Data 2,5mm², 400V


Other specification Grey insulating material, Wemid. 1-pole, 2-way terminal block. For mounting on rail
TS35

The above product is certified according to the flwg.
standard(s) Safety std.: EN 60947-7-1 :91 (see also EN 60947-1 :91)
EN 60998-2-1 August 1993 + OSM/IN :93
(see also EN 60998-1:93)
and EN 61210 :95

Validity The certificate is valid until 1 February 2010, provided that all signed certification
conditions are complied with, and that possible changes to the product are notified
to Nemko for acceptance prior to implementation. The validity time may be
reduced in case new standards are made applicable. The certificate also applies
as licence for use of Nemko's name and certification mark.

Variants This Certificate also covers variants with Position No. from 001 to 005
See next page(s)


Date of issue 31 January 2000



signature

Ragnar Køltzow

Head of section



signature

Glenn Sundbakken

No. P00100194

Order No. 199932194

Group 06 74500	Terminal blocks for incorporation, for fixation to a support; for industrial use etc. (EN 60947-7-1)
Position No	001
Model/type	WDK 2.5FFV
Data	1,0mm ² , 400V
Other specification	Grey insulating material, Wemid. 1-pole, 8-way push-on tab connection (8x2,8x0,8). For mounting on rail TS35
Position No	002
Model/type	WDK 2.5FV
Data	2,5/1,0mm ² , 400V
Other specification	Grey insulating material, Wemid. 1-pole, 2-way terminal block 2,5mm ² , and 1-pole, 4-way push-on tab connection 4x(2,8x0,8) max 1,0mm ² . For mounting on rail TS35.
Position No	003
Model/type	WDK 2.5F
Data	2,5/1,0mm ² , 400V
Other specification	Grey insulating material, Wemid. 2-pole, 2-way terminal block 2,5mm ² , and 2-pole, 4way push-on tab connection 4x(2,8x0,8) max 1,0mm ² . For mounting on rail TS35
Position No	004
Model/type	WDK 2.5V
Data	2,5mm ² , 400V
Other specification	Grey insulating material, Wemid. 1-pole, 4-way terminal block. For mounting on rail TS35
Position No	005
Model/type	WDK 2.5FF
Data	1,0mm ² , 400V
Other specification	Grey insulating material, Wemid. 2-pole, 8-way push-on tab connection 8x(2,8x0,8). For mounting on rail TS35