

CERTIFICATE OF COMPLIANCE

Certificate Number

E471884

Report Reference

E471884-20180118

Issue Date

2021-MAY-04

Issued to:

WEIDMULLER INTERFACE GMBH & CO KG
KLINGENBERGSTRASSE 26
DETMOLD, D-32758 GERMANY

**This certificate confirms that
representative samples of**

COMMUNICATIONS-, AUDIO/VIDEO-, DATA- AND
OTHER SIGNALING-CIRCUIT ACCESSORIES -
COMPONENT

See Addendum Page

Have been investigated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety:

UL 1863 - Communications-Circuit Accessories
CSA-C22.2 No. 182.4 - Plugs, Receptacles and Connectors for Communication Systems

Additional Information:

See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E471884
Report Reference E471884-20180118
Issue Date 2021-MAY-04

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

PCB Mount jack:

RJ45XXXXXX XXV XXXXX XX XXXX, RJ45XXXXXX XXX XXXXX XX LHXX,
RJ45XXXXXX XXU XXXXX XX XXXX, RJ45XXXXXX XXH XXXXX XX XXXX,
RJ45XXXXXX XXXX XXXXXXXXXX XX XXXX, RJ45XXXXXX XXXX XXXXXXXX/XX XX XXXX

Where digits 1-4 represent the design of jack RJ45. Digits 5-9 represents production performance category, where X can be C5, C6, C6A, C5e, M, G1, G10, U, MP, MP+, G1P, G1P+, G10P, G10P+. Digit 10 represents the assembly on PCB, where X can be R, S, T. Digits 11-12 represents the number of ports, where X can be 1, 12, 14, 16, 18, 21, 41, 61, 81. Digit 13 represents the direction and latch option, where X can be H, U, V, Y. Digits 14-16 represents the solder pin length, where X can be 1.4, 1.5, 1.6, 1.7, 1.8, 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7, 2.8, 2.9, 3.0, 3.1, 3.2, 3.3, 3.4, 3.5, 3.6. Digit 17 represents the shield tabs, where X can be E, N. Digit 18 represents the contact surface thickness, where X can be 1, 2, 3, 4, 5. Digits 19-23 represents the LED option, where X can be Y/G, G/Y, GY/GY, YG/YG, O/G, G/O, O/Y, Y/O, R/O, R/G, further combinations are possible. Digits 24-25 represents the packaging, where X can be TY, RL. Digits 26-29 represents the circuit type, where X can be SO, 01, 02, 03, 04, 05, 06, 07, 08. Digits 30-31 represents the color, where X can be BK, WH, BL.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

